

## Jeremias Model DWKL and SWKL



**CUT BACK FITTINGS and Easy Install Tip**

Jeremias, Inc., Marietta, GA

# Cut Back Fittings

Jeremias Model DWKL

We are now shipping our DWKL double wall fittings and APS Supports with the outer jacket cut back 1 inch on the male end.

This makes for an easier installation as the male inner is protruding and easy to guide into the female inner.



outer jacket  
cut back

male inner  
protruding

# Cut Back Fittings

Jeremias Model DWKL

During assembly, the locking band covers the joint.



# Cut Back Fittings

Jeremias Model DWKL

Once assembled, the locking band covers the joint and they appear the same as if the outer was not cut back.



# Installation

## Jeremias Model DWKL Installation Tip - Straight Lengths

For the straight pipe lengths, here is an easy way to extend that inner to make your install easier.

Place two 2x4's on the floor and line them up just far enough apart that they stop the insulation and the outer, and push down on the inner. You push down from the top of the female (flush) end in order to push the inner out of the male end.



# Installation

## Jeremias Model DWKL Installation Tip - Straight Lengths

Once the inner is pushed out of the male end, it will probably not be just right on the female end. So you will need to adjust the insulation to be flush with the outer on the female end, and the inner to be the desired height on the male end.

Turn your pipe around so that the male end is up and the female end is flat on the floor. Push down to make the insulation flush with the floor and the outer jacket, and adjust the male end to the desired height-protruding above the outer by about an inch and a half.



# Installation

Jeremias Model DWKL  
Installation Tip - Straight Lengths

Here is your finished pipe ready to be installed!

Easy to line up and insert that male end now.

